



2014 CTX700N SPECIFICATIONS*

ENGINE

Engine Type	670cc liquid-cooled parallel-twin
Bore and Stroke	73mm x 80mm
Induction	PGM-FI, 36mm throttle body
Ignition	Digital transistorized with electronic advance
Compression Ratio	10.7:1
Valve Train	SOHC; four valves per cylinder

DRIVE TRAIN

Transmission	Six-speed
Final Drive	Chain

CHASSIS / SUSPENSION / BRAKES

Front Suspension	41mm fork, 4.2 inches travel
Rear Suspension	Pro-Link® single shock; 4.3 inches travel
Front Brake	Single 320mm disc with two-piston caliper
Rear Brake	Single 240mm disc with single-piston caliper
Front Tire	120/70-17
Rear Tire	160/60-17

DIMENSIONS

Rake (caster angle)	27.7 degrees
Trail	114.0mm (4.4 inches)
Wheelbase	60.2 inches
Seat Height	28.3 inches
Curb Weight	478.4 pounds. Includes all standard equipment, required fluids and full tank of fuel—ready to ride
Fuel Capacity	3.17 gallons
Estimated Fuel Economy†	TBD

OTHER

Model ID	CTX700N
Emissions	Meets current EPA standards. Models sold in California meet current CARB standards and may differ slightly due to emissions equipment.
Available Colors	Cool Candy Red, Black

FACTORY WARRANTY INFORMATION

One Year	Transferable, unlimited-mileage limited warranty; extended coverage available with a Honda Protection Plan.
----------	---

*Specifications subject to change without notice.

†Honda's fuel economy estimates are based on EPA exhaust emission measurement test procedures and are intended for comparison purposes only. Your actual mileage will vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.

©2013 American Honda Motor Co., Inc. - Motorcycle Division